


## 50-B-54F - SPEEDLINE System Data Sheet - Version V1 (24-10-23)

SPEEDLINE 50mm 'C' Stud Partition @600mm Ctrs,  
with BG Gyproc 15mm SoundBloc F each side,  
50mm APR



### System Performance Breakdown

Fire Resistance:

BS476 Part 22:1987:

Test Ref & Date or Applied Ref & Report:

**60/60 Minutes (Integrity/Insulation).**

**BMT/FEP/F14106 - 29/07/2014 & BRE Report P102396-1011A**

Max Height:

**Refer to Speedline Specification Clause**

Thickness:

**82 mm.** (At Base Track, Excluding Finishes)


Duty Grade: BS 5234: Part 2:1992:

**Heavy - Annexes A-F**

Sound Insulation:

**40 R<sub>w</sub>dB**, Date Tested or Assessed Against - 50-B-54

## SRL



TESTED AT ONE OF THE UKAS  
ACCREDITED LABORATORIES  
BELOW

B.T.C (H-Ref on Graph)	
B.R.E	
AIRO	
S.R.L	

SPEEDLINE Drywall Systems, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH.

Tel: 0114 231 8030.

Email: [enquiries@speedlinedrywall.co.uk](mailto:enquiries@speedlinedrywall.co.uk)

(As per the requirements set out in ISO/IEC 17025:2017 regarding test data the results stated have been carried out by voestalpine Metsec plc as part of the contract to supply Speedline Metal Sections to SIG Plc)