


SE60-B-62 - SPEEDLINE System Data Sheet - Version V1 (24-10-23)

SPEEDLINE 60mm 'l' Stud Shaft Encasement @600mm Ctrs, with 2x BG Gyproc 15mm FireLine, BG Gyproc 19mm CoreBoard,




System Performance Breakdown

Fire Resistance: BS476 Part 22:1987: (Integrity/Insulation). Test Ref & Date or Applied Ref & Report: Max Height: Thickness: Duty Grade: BS 5234: Part 2:1992: Sound Insulation:

120/120 FromShaftSide, 90/90 FromLandingSide Minutes

BRE 302289 - BRE Report P102396-1012A Refer to Speedline Specification Clause 92 mm. (At Base Track, Excluding Finishes) Severe - Annexes A-F 41 R_wdB, Date Tested or Assessed Against -



SPEEDLINE Drywall Systems, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH. Tel: 0114 231 8030.

Email: enquiries@speedlinedrywall.co.uk

(As per the requirements set out in ISO/IEC 17025:2017 regarding test data the results stated have been carried out by voestalpine Metsec plc as part of the contract to supply Speedline Metal Sections to SIG Plc)