


AS92-K-154(100) - SPEEDLINE System Data Sheet - Version V1 (24-10-23)

SPEEDLINE 92mm Acoustic 'C' Stud Partition
@600mm Ctrs, with Knauf 15mm Soundshield Plus
each side, 100mm APR



System Performance Breakdown

Fire Resistance:

BS476 Part 22:1987:

Test Ref & Date or Applied Ref & Report:

Max Height:

Thickness:

Duty Grade: BS 5234: Part 2:1992:

Sound Insulation:

60/60 Minutes (Integrity/Insulation).


BRE 285458 - BRE Report P102396-1011B

Refer to Speedline Specification Clause

124 mm. (At Base Track, Excluding Finishes)

Severe - Annexes A-F

52 R_w dB, Date Tested or Assessed Against - 02/04/2014



TESTED AT ONE OF THE UKAS ACCREDITED LABORATORIES BELOW

B.T.C (H-Ref on Graph)	
B.R.E	
AIRO	
S.R.L	

Customer: Metsec plc Hespsec Division

BTC 18668A: Page 9 of 12



SPEEDLINE Drywall Systems, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH.

Tel: 0114 231 8030.

Email: enquiries@speedlinedrywall.co.uk

(As per the requirements set out in ISO/IEC 17025:2017 regarding test data the results stated have been carried out by voestalpine Metsec plc as part of the contract to supply Speedline Metal Sections to SIG Plc)