


## 70-K-56 - SPEEDLINE System Data Sheet - Version V1 (24-10-23)

SPEEDLINE 70mm 'C' Stud Partition @600mm Ctrs,  
with Knauf 15mm Fire Panel each side



### System Performance Breakdown

Fire Resistance:

BS476 Part 22:1987:

Test Ref & Date or Applied Ref & Report:

Max Height:

Thickness:

Duty Grade: BS 5234: Part 2:1992:

Sound Insulation:

**60/60 Minutes** (Integrity/Insulation).

**BRE 248834 - BRE Report P102396-1011B**


**Refer to Speedline Specification Clause**

**102 mm.** (At Base Track, Excluding Finishes)

**Heavy - Annexes A-F**

**37 R<sub>w</sub>dB**, Date Tested or Assessed Against - 70-K-51

### Sound Insulation



TESTED AT ONE OF THE UKAS  
ACCREDITED LABORATORIES  
BELOW

|                           |  |
|---------------------------|--|
| B.T.C<br>(H-Ref on Graph) |  |
| B.R.E                     |  |
| AIRO                      |  |
| S.R.L                     |  |

SPEEDLINE Drywall Systems, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH.

Tel: 0114 231 8030.

Email: [enquiries@speedlinedrywall.co.uk](mailto:enquiries@speedlinedrywall.co.uk)

(As per the requirements set out in ISO/IEC 17025:2017 regarding test data the results stated have been carried out by voestalpine Metsec plc as part of the contract to supply Speedline Metal Sections to SIG Plc)