


## TWI92-S-60(2x50)(250) - SPEEDLINE System Data Sheet - Version V1 (24-10-23)

Twin SPEEDLINE 92mm 'I' Stud Partition @600mm Ctrs, with 2x Siniat GTEC 15mm dB Board each side, 50+50mm APR



### System Performance Breakdown

Fire Resistance:

BS476 Part 22:1987:

Test Ref & Date or Applied Ref & Report:

Max Height:

Thickness:

Duty Grade: BS 5234: Part 2:1992:

Sound Insulation:

90/90 Minutes (Integrity/Insulation).


BRE-P100456-1085 - BRE Report P102396-1011C

Refer to Speedline Specification Clause

250 mm. (At Base Track, Excluding Finishes)

Severe - Annexes A-F

69  $R_w$ dB, -8Ctr Date Tested or Assessed Against - TWI50-S-60(2x50)(200)



TESTED AT ONE OF THE UKAS ACCREDITED LABORATORIES BELOW

B.T.C (H-Ref on Graph)

B.R.E

AIRO

S.R.L

Customer: Metsec plc Hepsec Division

BTC 18508A: Page 9 of 12



SPEEDLINE Drywall Systems, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH.

Tel: 0114 231 8030.

Email: [enquiries@speedlinedrywall.co.uk](mailto:enquiries@speedlinedrywall.co.uk)

(As per the requirements set out in ISO/IEC 17025:2017 regarding test data the results stated have been carried out by voestalpine Metsec plc as part of the contract to supply Speedline Metal Sections to SIG Plc)