

# Drywall Angle

L-shaped steel Section angles used for a variety of applications within Speedline systems.

## MATERIAL PROPERTIES

### Product Material

DX51D Steel

### Product Finish

140 micron galvanised coating

### Fire Classification

A1

### Tensile Strength

270-500N/mm<sup>2</sup>

### Density

7.85g/cm<sup>3</sup>

### Minimum Elongation A80%

22% (A80)



## PRODUCT APPLICATION

Speedline Angles can be used for many general applications in ceilings, dry lining and also for cloaking deflection heads in partitioning systems.

## FEATURES AND BENEFITS

- For use in multiple Speedline systems across a variety of sectors
- Available in various sizes including equal and unequal angles in 3m and 3.6m lengths
- Can be cut using tin snips or power tools
- Dimensionally accurate
- Weighing from just 0.86kg for our smallest size, they are lightweight and easy to manoeuvre
- For more specific technical information about our Speedline Tracks or any of our systems, please view or download our Speedline manual or contact our technical team
- Also available in Speedline Low Carbon (0.7mm gauge only)

| Product Code | Product Range | Width | Height | Gauge | Stock Length | Weight per Length |
|--------------|---------------|-------|--------|-------|--------------|-------------------|
| 10027163     | SSL06         | 25mm  | 25mm   | 0.7mm | 3000mm       | 0.86kg            |
| 10027164     | SSL06         | 25mm  | 25mm   | 0.7mm | 3600mm       | 0.89kg            |
| 10027166     | SL12          | 50mm  | 25mm   | 0.7mm | 3000mm       | 1.15kg            |
| 10027167     | SL12          | 50mm  | 25mm   | 0.7mm | 3600mm       | 1.38kg            |
| 10027168     | SL13          | 50mm  | 50mm   | 0.7mm | 3000mm       | 1.59kg            |
| 10027169     | SL13          | 50mm  | 50mm   | 0.7mm | 3600mm       | 1.88kg            |
| 10027170     | SL26          | 50mm  | 50mm   | 1.5mm | 3600mm       | 3.68kg            |