SPEEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml,

600ml & 900ml

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Sealant . For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Speedline Adsetts House,16 Europa View, Sheffield Business Park S9 1XH Sheffield - South Yorkshire - United Kingdom Phone: +44 (0) 1173 013 634 enquiries@speedlinedrywall.co.uk www.speedlinedrywall.co.uk

1.4 Emergency telephone number: +44 (0) 1173 013 634 (Monday-Friday 9am-5pm GMT)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture: **GB CLP Regulation:** The product is not classified as hazardous according to GB CLP Regulation. 2.2

Label elements:

GB CLP Regulation: Hazard statements:

Non-applicable

Precautionary statements:

Non-applicable

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol -3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. EUH210: Safety data sheet available on request.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	13463-67-7	Titanium dioxide (aerodynamic diameter ≥ 10 μm)	1 - <5 %
CAS: 2	2634-33-5	1,2-benzisothiazol-3(2H)-one Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger 🚺 🐼 🎕	0.01 - <0.1 %
CAS: 8	55965-84-9	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	0.001 - <0.01 %



PEEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification			M-factor
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothi	azol-3-one (3:1)	Acute	100
CAS: 55965-84-9		Chronic	100
Identification	Spe	cific concentr	ation limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5	% (w/w) >=0.05: Skin Sens.	1 - H317	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1) CAS: 55965-84-9	% (w/w) >=0.6: Skin Corr. 1 0.06<= % (w/w) <0.6: Skin I % (w/w) >=0.6: Eye Dam. 1 0.06<= % (w/w) <0.6: Eye Ir % (w/w) >=0.0015: Skin Ser	rrit. 2 - H315 - H318 rrit. 2 - H319	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

Most important symptoms and effects, both acute and delayed: 4.2

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...). Additional provisions:



EEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 **Environmental precautions:**

It is recommended to avoid environmental spillage of both the product and its container.

Methods and material for containment and cleaning up: 6.3

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections: 6.4

See sections 8 and 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

See Section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:



EEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

EH40/2005 Workplace ex	posure limits, fourth edition,	published 2020:

Identification	Occupational exposure limits		
Titanium dioxide (aerodynamic diameter ≥ 10 µm)	WEL (8h)		4 mg/m ³
CAS: 13463-67-7	WEL (15 min)		

DNEL (Workers):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0.966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6.81 mg/m³	Non-applicable

DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0.345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1.2 mg/m ³	Non-applicable

PNEC:

Identification				
1,2-benzisothiazol-3(2H)-one	STP	1.03 mg/L	Fresh water	0.00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0.000403 mg/L
EC: 220-120-9	Intermittent	0.0011 mg/L	Sediment (Fresh water)	0.0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.00499 mg/kg

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.
E	Body protection		

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.



SPEEDLINE DRYWALL SYSTEMS | Part of See DRYWALL SYSTEMS | Part of See DRYWALL SYSTEMS | Part of See

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)							
Picto	gram	PPE		Remarks			
		Anti-slip work shoes	to the product for professional/in	terioration. For periods of prolonged exposure ndustrial users CE III is recommended, in in EN ISO 20345:2012 y EN 13832-1:2007			
F Additiona	F Additional emergency measures						
Eme	gency measure	Standards	Emergency measure	Standards			
Eme	rgency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:20	11 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011			
Environme	ital exposure c	ontrols:					
spillage of b The Volatile V.O.C. (oth the product a Organic Comp Supply):	and its container. For additional i bounds in Paints, Varnishes ar 0 % weight	nformation see subsection 7.1.I d Vehicle Refinishing Produc				
V.O.C. d	ensity at 20 °C:	0.02 kg/m³ (0.02 g/	-)				
SECTION 9: PH	YSICAL AND	CHEMICAL PROPERTIES					
0.1 Information	on basic physi	cal and chemical properties:					
		e the product datasheet.					
Appearance							
Physical sta		Ligu	Liquid Paste				
Appearance							
Colour:			White				
Odour:			Odourless				
Odour thres	nold:		Non-applicable *				
Volatility:							
-	at atmospheric	pressure: Non	Non-applicable * Non-applicable *				
• •	sure at 20 °C:						
	sure at 50 °C:		Non-applicable *				
	rate at 20 °C:		-applicable *				
Product des							
Density at 2	-	ca.	600 kg/m³				
-	sity at 20 °C:	ca.	-				
	cosity at 20 °C:		-applicable *				
-	scosity at 20 °C:		-applicable *				
	scosity at 40 °C:		>20.5 mm²/s Non-applicable * ca. 8.5 - 9.5 Non-applicable *				
Concentratio	-						
pH:							
Vapour dens	ity at 20 ⁰C:						
	fficient n-octano		-applicable *				
Solubility in	water at 20 °C:		-applicable *				
Solubility pro			-applicable *				
	on temperature:		Non-applicable *				
Decompositi		NUL	applicable				
-	/freezing point:		-applicable *				

Version: 4 (Replaced 3)

Revised: 21/09/2023



SPEEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SEC	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)				
	Flammability:				
	Flash Point:	>100 °C			
	Flammability (solid, gas):	Non-applicable *			
	Autoignition temperature:	Non-applicable *			
	Lower flammability limit:	Non-applicable *			
	Upper flammability limit:	Non-applicable *			
	Particle characteristics:				
	Median equivalent diameter:	Non-applicable			
9.2	Other information:				
	Information with regard to physical hazard classe	s:			
	Explosive properties:	Non-applicable *			
	Oxidising properties:	Non-applicable *			
	Corrosive to metals:	Non-applicable *			
	Heat of combustion:	Non-applicable *			
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *			
	Other safety characteristics:	New weekster			
	Surface tension at 20 °C:	Non-applicable *			
	Refraction index:	Non-applicable *			
	*Not relevant due to the nature of the product, not providing information property of its hazards.				

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:



EDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:
 - Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as
 - it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	cute toxicity	Genus
Titanium dioxide (aerodynamic diameter ≥ 10 μm)	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87.12 mg/kg	Rabbit
	LC50 inhalation	0.33 mg/L (4 h)	Rat

ATE mix

Ingredient(s) of unknown toxicity

SPEEDLINE DRYWALL SYSTEMS | Part of Section Se

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Oral	>5000 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
1,2-benzisothiazol-3(2H)-one	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 2634-33-5	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Titanium dioxide (aerodynamic diameter ≥ 10 µm)		1000 mg/L	Danio rerio	Fish
CAS: 13463-67-7	NOEC	1 mg/L	Corbicula fluminea	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
1,2-benzisothiazol-3(2H)-one	BCF	2
CAS: 2634-33-5	Pow Log	1.45
	Potential	Low

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class			
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	Non dangerous			
Type of waste:					
Non-applicable					
Waste management (disposal and evaluation):					



SPEEDLINE DRYWALL SYSTEMS | Part of Sec DRYWALL SYSTEMS | Part of

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECT

TON 14: 1	FRANSPORT INFORMATION	١
Transpor	t of dangerous goods by land:	
-	ard to ADR 2023 and RID 2023:	
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5 14.6	Environmental hazards:	No
14.0	Special precautions for user Tunnel restriction code:	New explicable
	Physico-Chemical properties:	Non-applicable see section 9
447	, , ,	
14.7	Transport in bulk according to Annex II of Marpol and the IBC	Non-applicable
	Code:	
Transpor	t of dangerous goods by sea:	
With rega	rd to IMDG 40-20:	
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5	Marine pollutant:	No
14.6	Special precautions for user Special regulations:	Non-applicable
	1 0	Non-applicable
	EmS Codes: Physico-Chemical properties:	see section 9
	Limited quantities:	Non-applicable
	Segregation group:	Non-applicable
14.7	Transport in bulk according to	Non-applicable
	Annex II of Marpol and the IBC	
T	Code:	
-	t of dangerous goods by air:	
0	rd to IATA/ICAO 2023:	
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es): Labels:	Non-applicable Non-applicable
14.4	Packing group:	Non-applicable
14.4	Environmental hazards:	Non-applicable
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according to	Non-applicable
	Annex II of Marpol and the IBC Code:	



PEEDLINE 10645882, 10645879, 10645880 - Speedline Intumescent Sealant 310ml, 600ml & 900ml

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable - Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020. The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction. **Classification procedure:** Non-applicable Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

Safety data sheet According to UK REACH



SPEEDLINE DRYWALL SYSTEMS | Part of Sec DRYWALL SYSTEMS | Part of

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.