

Thermal Laminate Board EPS

DoP Reference: Speedline-Thermal laminate board-EPS-V2-26-10-2022-UKCA-DOP

Replaces DoP Reference: Speedline-Thermal laminate board-EPS-V1-01-06-2022-UKCA-DOP


- UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:** Thermal Laminate Board EPS
- TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**
2400x1200x25.5mm Type A 9.5-EPS-16
2400x1200x32.5mm Type A 9.5-EPS-23
2400x1200x42.5mm Type A 9.5-EPS-33
- INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT AS FORESEEN BY THE MANUFACTURER**
Class 1 thermal/acoustic insulation composite panel made of an insulating material laminated to gypsum boards as internal insulation (thermal and/or acoustic) of walls
- NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**
SIG Trading Ltd, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH
- NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**
NOT RELEVANT
- SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**
4
- NAME AND IDENTIFICATION NUMBER OF THE APPROVED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A DESIGNATED STANDARD**
N/A
- NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**
N/A
- DECLARED PERFORMANCE ACCORDING TO:**
BS EN 13950:2014

Essential Characteristics	Performance	Designated Standard or Technical Specification
Reaction to fire – R2F	NPD	BS EN 13950:2014
Flexural Strength - F	Pass	BS EN 13950:2014
Water vapour resistance factor - μ	NPD	BS EN 13950:2014
Thermal resistance (m ² K/W) - 25.5mm - 32.5mm - 42.5mm	0.471 0.655 0.918	BS EN 13950:2014
Impact resistance	NPD	BS EN 13950:2014
Airborne sound insulation - R	NPD	BS EN 13950:2014
Acoustic absorption - α	NPD	BS EN 13950:2014
Dangerous substances - DS	NPD	BS EN 13950:2014

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

NPD = No Performance Declared

Signed for and on behalf of SPEEDLINE DRYWALL, SIG Trading Ltd:



Steve Marr - SIG UK Compliance Director
26/10/2022, Sheffield