

Thermal Laminate Board XPS

DoP Reference: Speedline-Thermal laminate board-XPS-V2-26-10-2022-UKCA-DOP

Replaces DoP Reference: Speedline-Thermal laminate board-XPS-V1-01-06-2022-UKCA-DOP

- 1. UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:** Thermal Laminate Board XPS
- 2. TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**
2400x1200x29.5mm Type A 9.5-XPS-20
2400x1200x39.5mm Type A 9.5-XPS-30
2400x1200x44.5mm Type A 9.5-XPS-35
2400x1200x49.5mm Type A 9.5-XPS-40
- 3. INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT AS FORESEEN BY THE MANUFACTURER**
Class 1 thermal/acoustic insulation composite panel made of an insulating material laminated to gypsum boards as internal insulation (thermal and/or acoustic) of walls
- 4. NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**
SIG Trading Ltd, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH
- 5. NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**
NOT RELEVANT
- 6. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**
4
- 7. NAME AND IDENTIFICATION NUMBER OF THE APPROVED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A DESIGNATED STANDARD**
N/A
- 8. NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**
N/A
- 9. DECLARED PERFORMANCE ACCORDING TO:**
BS EN 13950:2014

Essential Characteristics	Performance	Designated Standard or Technical Specification
Reaction to fire – R2F	NPD	BS EN 13950:2014
Flexural Strength - F	Pass	BS EN 13950:2014
Water vapour resistance factor - μ	NPD	BS EN 13950:2014
Thermal resistance (m ² K/W)		
- 29.5mm	0.656	BS EN 13950:2014
- 39.5mm	0.959	
- 44.5mm	1.111	
- 49.5mm	1.262	
Impact resistance	NPD	BS EN 13950:2014
Airborne sound insulation - R	NPD	BS EN 13950:2014
Acoustic absorption - α	NPD	BS EN 13950:2014
Dangerous substances - DS	NPD	BS EN 13950:2014

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

NPD = No Performance Declared

Signed for and on behalf of SPEEDLINE DRYWALL, SIG Trading Ltd:



Steve Marr - SIG UK Compliance Director
26/10/2022, Sheffield