

# Metal Corner Bead Tape

Roll of kraft paper specifically made for corner joints, punched all along on both sides and reinforced by two flexible aluminium zinc coated strips.

<b>Product Code</b>	10039684
<b>Dimensions</b>	50mm x 30m
<b>Weight</b>	1.9kg
<b>Colour</b>	White
<b>Pack Size</b>	10

## MATERIAL

Kraft paper, Al-Zn coated metal strips  
(Metal Strip Thickness: 0.37mm, Metal Strip Width: 11mm)

## RECOMMENDED / APPLICATION

### Suitable Surfaces

Plasterboard walls and ceilings

### Product Application

Used to reinforce external corners/edges of plasterboard walls and ceilings.

## STORAGE INSTRUCTIONS

Products must be stored in a clean, dry place, and in a well ventilated area. Keep away from direct sunlight and excessive humidity.

### Storage Temperature

5°C to 25°C

### Shelf Life

Not Applicable if stored correctly

### Packaging

Cardboard box with side opening

## APPLICATION INSTRUCTIONS

### Surface Preparation

Surfaces must be clean and dust free.

### Application Temperature

5°C to 30°C

## Application Instructions

1. Make sure that the plasterboard surfaces are clean and dust free.
2. Using a taping knife, coat the corner to be reinforced with 3mm of filling compound.
3. Cut the tapes to length and fold the tape, with metal side inward, then push into the compound.
4. Remove excess filling compound with the taping knife.
5. Refill over tapes with filling compound.
6. Once dry, recoat with a finishing joint compound.
7. Sand lightly with a mild abrasive when dry.



## TECHNICAL PROPERTIES

Strips resistance to salt spread test: more than 48h (EN ISO 9227)

Paper yield strength resistance: 5.239 N/mm<sup>2</sup> (EN 13963)

Dimensional stability: (EN 13963)  
- Length: -0.1 %  
- Width: 1.2 %

Steel band yield strength resistance: 690 N/mm<sup>2</sup>

## FEATURES AND BENEFITS

- Reinforced with two flexible aluminium - zinc coated strips
- Each roll contains 30m of tape