

Metal Nail-In Anchor

A lightweight metal through fixing for use in concrete, solid brickwork and stone.

USES

Metal roof profiles
Pipework installation
Cable trays
Cable conduits and wires
Cladding and panelling and installation of other external trim.

SUITABLE SURFACES

Non-cracked concrete C20/25-C50/60

Not recommended for ceiling applications and suspension systems.



PRODUCT INFORMATION

Material

Hardened Steel

Product Finish

Zinc Coating

APPLICATION INSTRUCTIONS

1. Drill a hole of required diameter and depth
2. Insert fixing through fixture into hole until fixing depth is reached
3. Hammer-in the nail. Drive the expansion wedge in flush to the nail head.

FEATURES AND BENEFITS

- Low-profile mushroom head provides a smooth finish and tamper proof fastening
- Consistent load values ensure light-duty fastenings in concrete and masonry
- Impact expansion by hammer, no setting tool is needed
- Designed for easy push-through fastenings, even in bottomless holes
- Available in various lengths from 30mm to 60mm

Product Code	Width	Length	Box Quantity	Thread Diameter	Thread Length	Fixture Max Thickness	Fixture Hole Diameter
10091882	6mm	40mm	100	6mm	40mm	10mm	7mm
10091883	6mm	50mm	100	6mm	50mm	20mm	7mm
10091884	6mm	60mm	100	6mm	65mm	35mm	7mm