

Nylon Hammer Screw Fixing

Pre-assembled nylon hammer fixings for fixing into concrete and solid masonry.

USES

Timber and Metal Battens
Drywall Structures
Skirting and Dado Railing
Cable Clamps
Pipe Clamps.

SUITABLE SURFACES

Concrete
Solid Brick
Solid Sand-lime Brick
Hollow Sand-lime Brick
Lightweight Concrete Block
Hollow Lightweight Concrete
Block, Aerated Concrete Block



PRODUCT INFORMATION

Box Quantity

100

Material

Hardened Steel

Product Finish

Bright Zinc Plated (BZP)

APPLICATION INSTRUCTIONS

1. Drill a hole of required diameter
2. Insert FX plug into hole through fixture
3. Hammer the nail into the plastic sleeve until fixing is secure and flush with the fixture.

FEATURES AND BENEFITS

- Rapid hammer-set installation reduces the time required and allows for cost-effective, high-volume installation
- The range of product lengths and diameters with countersunk head type ensures availability of the correct fixing
- Designed for push-through installation
- Available in various lengths from 30mm to 120mm

Product Code	Width	Length	Plug Diameter	Nail Diameter	Nail Length	Fixture Max Thickness	Fixture Hole Diameter	Diameter Head
10091161	5mm	30mm	4.9mm	3.3mm	33mm	5mm	6mm	8.5mm
10091164	6mm	40mm	5.9mm	3.8mm	44mm	11mm	7mm	10mm
10091165	6mm	50mm	5.9mm	3.8mm	54mm	21mm	7mm	10mm
10091166	6mm	60mm	5.9mm	3.8mm	64mm	31mm	7mm	10mm
10091169	8mm	60mm	7.9mm	4.8mm	66mm	20mm	9mm	11.5mm
10091168	6mm	80mm	5.9mm	4.8mm	84mm	51mm	9mm	10mm
10091171	8mm	80mm	7.9mm	4.8mm	86mm	40mm	9mm	11.5mm
10091174	8mm	100mm	7.9mm	4.8mm	106mm	60mm	9mm	11.5mm
10091175	8mm	120mm	7.9mm	4.8mm	126mm	80mm	9mm	11.5mm