

# Paper Joint Tape

Roll of kraft paper which has been sanded, micro-perforated and prefolded.

<b>Product Code</b>	10003608
<b>Dimensions</b>	50mm x 150m
<b>Weight</b>	0.25kg
<b>Colour</b>	White
<b>Pack Size</b>	10

## MATERIAL

Bleached long fiber kraft paper

## RECOMMENDED / APPLICATION

### Suitable Surfaces

Plasterboard joints

### Product Application

Straight or Tapered Edge joints between plasterboards (wall partitions and ceilings).

## STORAGE INSTRUCTIONS

Products must be stored in a clean, dry place, and in a well ventilated area. Keep away from direct sunlight and excessive humidity.

### Storage Temperature

5°C to 25°C

### Shelf Life

Not Applicable if stored correctly

### Packaging

Cardboard Core

## APPLICATION INSTRUCTIONS

### Surface Preparation

Surfaces must be clean and dust free.

### Application Temperature

5°C to 30°C

## Application Instructions

1. Make sure that the plasterboard surfaces are clean and dust free.
2. Using a taping knife, coat the board joint between two plasterboards with 3mm of filling compound.
3. Cut the tape to length and push into compound.
4. Refill over tapes with compound.
5. Remove excess compound with the taping knife.
6. Once dry, recoat with a finishing joint compound.
7. Sand lightly with a mild abrasive when dry.



## TECHNICAL PROPERTIES

Tensile strength Resistance: 5.239 N/mm<sup>2</sup>

Dimensional stability:

- Length: < 0.4%
- Width: < 2.5%

## FEATURES AND BENEFITS

- Pre-folded in the centre helping to position the tape easily when needed
- Each roll contains 150m of tape