

# Self Adhesive Plasterboard Scrim Tape

Roll of self adhesive fibreglass mesh tape.

<b>Product Code</b>	10039680
<b>Dimensions</b>	48mm x 90m
<b>Weight</b>	0.288kg
<b>Colour</b>	White
<b>Pack Size</b>	24

## MATERIAL

Fiberglass, Acrylic Copolymer

## RECOMMENDED / APPLICATION

### Suitable Surfaces

Plasterboard joints

### Product Application

Plasterboard walls and ceilings.

## STORAGE INSTRUCTIONS

Products must be stored in a clean, dry place, and in a well ventilated area. Keep away from direct sunlight and excessive humidity.

### Storage Temperature

5°C to 25°C

### Shelf Life

12 Months

### Packaging

Roll is wrapped in shrink-film with a product label applied to the top side

## APPLICATION INSTRUCTIONS

### Surface Preparation

Surfaces must be clean and dust free.

### Application Temperature

5°C to 30°C

## Application Instructions

1. Make sure that joint is clean without dust, then apply the self-adhesive side directly onto the joint.
2. Cover the tape immediately and completely with a thin coat of plaster (5 - 10 cm wide) and allow it to dry.
3. To finish, cover with a further coat of plaster (15 - 20 cm wide).



## TECHNICAL PROPERTIES

Tensile Strength (min) [N / 5 cm] - 30%
Warp 400 Weft 800
Weight (g / m <sup>2</sup> ) +/- 10%
60
DPU - Deposit per Unit (PES + coating + PSA) (%) +/-10%
38
Setting (ends / 10cm) Warp 35.4 Weft 35.4

## FEATURES AND BENEFITS

- Eliminates blisters and bubbles in the jointing compound
- Each roll contains 90m of tape