

Wall & Ceiling Liner

C-shaped steel section.

MATERIAL PROPERTIES

Product Material

DX51D Steel

Product Finish

140 micron galvanised coating

Fire Classification

A1

Tensile Strength

270-500N/mm²

Density

7.85g/cm³

Minimum Elongation A80%

22% (A80)



PRODUCT APPLICATION

Used as part of the Speedline Wall Liner Systems for installing plasterboard to masonry walls allowing space for insulation. Can also be used on concrete soffits and timber joints. Also used as part of the Speedline Column & Beam encasement systems.

FEATURES AND BENEFITS

- Can also be used on concrete soffits and timber joints
- Also used as part of the Speedline Column & Beam Encasement systems
- With a range of fixing brackets available, cavities from 25mm up to 175mm can be formed
- With the addition of Speedline Thermal Laminates, the thermal performance of the substrate can be improved
- Can be used where plaster or direct bond systems are not suitable
- Bespoke lengths available subject to minimum order quantities or can be cut to length using tin snips or power tools
- Dimensionally accurate
- Weighing under 1kg for our shortest length, they are lightweight and easy to manoeuvre
- Also available in Speedline Low Carbon

Product Code	Product Range	Width	Height	Gauge	Stock Length	Weight per Length
10027324	SWL507	45mm	18mm	0.5mm	2400mm	0.83kg
10027325	SWL507	45mm	18mm	0.5mm	2700mm	0.93kg
10027326	SWL507	45mm	18mm	0.5mm	3000mm	1.04kg
10027329	SWL507	45mm	18mm	0.5mm	3600mm	1.25kg