

# Wall & Ceiling Perimeter Track

U-shaped steel section with uneven legs.

## MATERIAL PROPERTIES

### Product Material

DX51D Steel

### Product Finish

140 micron galvanised coating

### Fire Classification

A1

### Tensile Strength

270-500N/mm<sup>2</sup>

### Density

7.85g/cm<sup>3</sup>

### Minimum Elongation A80%

22% (A80)



## PRODUCT APPLICATION

Used as part of the Speedline Wall Liner Systems for installing plasterboard to masonry walls allowing space for insulation. Can also be used on concrete soffits and timber joints. Also used as part of the Speedline Column & Beam encasement systems.

## FEATURES AND BENEFITS

- Can also be used on concrete soffits and timber joints
- Also used as part of the Speedline Column & Beam Encasement systems
- With the addition of Speedline Thermal Laminates, the thermal performance of the substrate can be improved
- Can be used where plaster or direct bond systems are not suitable
- Can be cut using tin snips or power tools
- Dimensionally accurate
- Available in 3m lengths
- Weighing under 1kg, they are lightweight and easy to manoeuvre
- Also available in Speedline Low Carbon

---

Product Code	Product Range	Width	Height	Gauge	Stock Length	Weight per Length
10027323	SWL60	19mm	18/28mm	0.5mm	3000mm	0.73kg